

TRIUMPH

Full Height Industrial Turnstile



The Triumph Turnstile is used to control high volumes at high risk areas. It is suitable for both exterior and interior use in severe conditions, with no routine maintenance required. Available in 3-arm (120°), 4-arm (90°) or 5-arm (72°).

FEATURES

- Bi-direction scanning
- Rotalok rotational locking mechanism
- Self-centering rotation system
- Does not lock in the event of a power failure
- Corrosion resistant
- Very quiet
- Self-lubricating
- Battery backup (optional)
- Anti-climb protection (optional)

SPECIFICATIONS

Power	220 V AC (110 V AC on request)
Frequency	50Hz / 60 Hz
Power Consumption	50 W (single) / 100 W (double)
Solenoid Voltage	24 V DC (12 V DC on request)
Logic Voltage	24 V DC
Dimensions	Single: 1400 x 2125 mm (WxH) / 1430 x 2250 mm (WxH) (recommended opening size) Double: 2150 x 2125 mm (WxH) / 2180 x 2250 mm (WxH) (recommended opening size)
Rotor Diameter	1200 mm
Rotor Arm Configuration	3 / 4 / 5 arm
Rotor Arms	32 mm diameter U-tube arms spaced 165 mm apart
Weight	Single: 160 kg / Double: 255 kg

