

# E2S SIREN RANGE



Compact and robust, the E2S range of sirens is ideal for general signalling, including fire, security and process control.

## FEATURES

- IP66
- Sound output can be adjusted
- 4 x different models available
- Available in red or grey
- 32/45 User selectable tones with 3 stage alarm options, dependant on model

## SPECIFICATIONS

Voltage	10-30V DC   24V AC   110V AC   220V AC
Duty Cycle	Continuous Rated
Sound Output	A100: 100dB(A) at 1m A105: 112dB(A) at 1m A112: 119dB(A) at 1m A121: 126dB(A) at 1m
Sound Frequency	340/2400Hz (depends on tone selection)
Range	A100: 300m in still air on open field A105: 500m in still air on open field A112: 800m in still air on open field A121: 1000m in still air on open field
Current Consumption	A100: 10-30V DC - 25mA   24V AC - 40mA   110V AC - 13mA   220V AC - 13mA A105: 10-30V DC - 25mA   24V AC - 40mA   110V AC - 20mA   220V AC - 15mA A112: 10-30V DC - 200mA   24V AC - 500mA   110V AC - 100mA   220V AC - 60mA A121: 10-30V DC - 950mA   24V AC - 1000mA   110V AC - 240mA   220V AC - 15mA
Weight	A100: 370g   A105: 1kg   A112: 2.1kg   A121: 2.7kg
Packing Dimensions	A100: 110 x 110 x 90mm A105: 150 x 150 x 140mm A112: 200 x 200 x 160mm A121: 220 x 200 x 220mm



OFTEN SOLD WITH

ORBIS 15A-20A 7-day programmable electronic timer

